

Fastening material

Polycarbonate diffuser 60w hublot60

471



polycarbonate diffuser 60w

	471
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for built-in mounting	No
Suitable for surface mounting	No
Suitable for light line configuration	No
Suitable for workplace according to EN 12464-1	No
Lamp type	Other
With light source	No
Suitable for number of light sources	1
Lamp holder	E27
Housing material	Plastic
Housing colour	White
Material cover	Plastic, transparent
Type of grid	None
Voltage type	AC/DC
Type of control gear	Not required
With control gear	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming phase cut-off (trailing edge)	No

Polycarbonate diffuser 60w hublot60

	471
Dimming phase cut-on (leading edge)	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
Light distributor	Reflector
Light distribution	Symmetric
Beam angle	Open beam/diffuse
Light outlet	Direct
Degree of protection (NEMA)	Other
Impact strength	IK09
Protection class according to IEC 61140	II
Luminaire with limited surface temperature, sign "D"	No
Suitable for emergency lighting	No
With movement sensor	No
With light sensor	No
Covering of the luminaire with thermally insulating	No
With air slots	No
Filament test according to IEC 60695-2-11	750 °C - 30 s
Max. system power	100 W
Rated luminous flux according to IEC 62722-2- 1	200 lm
Colour of light	White
Colour temperature	2000 - 2000 K
Colour rendering index CRI	80-89
Type of wiring	Ending
Number of poles	1
Connection type	Screwed terminal

Brand	JSL
Art. N°	471
Colour	Blanc_Transparent
Sales unit	pc
EAN PCE	5601859012937
EAN QTY PCE	1
EAN QTY C02	30
Intrastat code	94051021