


ERM



Termoplástico
Termoplastico
Thermoplastic
Thermoplastique



-15°C
+90°C



Cinza
Gris
Grey
Gris



Resistência ao esmagamento
Resistencia al aplastamiento
Crush Resistance
Résistance à l'écrasement



Resistência choques mecânicos
Resistencia a golpes mecánicos
Mechanical shocks Resistance
Résistance aux chocs mécaniques

EN61386-22



Tubo Jotagris "ERM"
Tubo Jotagris "ERM"
Semi-rigid conduit f. concrete
Conduit semi-rigide ICTL
pour le beton



Fortes
Fuerτες
Heavy loads
Jauge fort




EN61386-1
EN61386-22
EN50267-2-2

Ref.	Cod.	Diam. Ext.	Diam. Int. *	Newtons	Cod.	Joules	Cod.	Temp.	Cod.
ERM16	4432	16	12	1250	4	6	4	-15°C +90°C	32
ERM20	4432	20	16,2	1250	4	6	4	-15°C +90°C	32
ERM25	4432	25	20,2	1250	4	6	4	-15°C +90°C	32
ERM32	4432	32	25,4	1250	4	6	4	-15°C +90°C	32
ERM40	4432	40	32,5	1250	4	6	4	-15°C +90°C	32

* Valor indicativo | Indicative value | Valeur indicative

ERM Com Guia De Aço | ERM Con Guia De Acero Semi Rigid With Steel Wire | Semi Rigide . Tire-fil En Acier



Tubo Jotagris "ERM" com guia de aço
Tubo Jotagris "ERM" con guia de acero
Semi-rigid conduit with steel wire
Conduit semi-rigide ICTL
pour le beton avec tire-fil en acier



Fortes
Fuerτες
Heavy loads
Jauge fort



EN61386-1
EN61386-22
EN50267-2-2

Ref.	Cod.	Diam. Ext.	Diam. Int. *	Newtons	Cod.	Joules	Cod.	Temp.	Cod.
ERM16G	4432	16	12	1250	4	6	4	-15°C +90°C	32
ERM20G	4432	20	16,2	1250	4	6	4	-15°C +90°C	32
ERM25G	4432	25	20,2	1250	4	6	4	-15°C +90°C	32
ERM32G	4432	32	25,4	1250	4	6	4	-15°C +90°C	32
ERM40G	4432	40	32,5	1250	4	6	4	-15°C +90°C	32

* Valor indicativo | Indicative value | Valeur indicative

ERFE



Tubo Jotagris "ERFE"
Tubo Jotagris "ERFE"
Semi-rigid conduit f. concrete
Conduit semi-rigide ICTL
pour le beton



Médias
Medias
Medium loads
Jauge Medium



Fortes
Fuerτες
Heavy loads
Jauge fort



Ref.	Cod.	Diam. Ext.	Diam. Int. *	Newtons	Cod.	Joules	Cod.	Temp.	Cod.
ERFE16	3432	16	12,4	750	3	6	4	-15°C +90°C	32
ERFE20	3432	20	16,6	750	3	6	4	-15°C +90°C	32
ERFE25	3432	25	20,6	750	3	6	4	-15°C +90°C	32
ERFE32	3432	32	25,9	750	3	6	4	-15°C +90°C	32
ERFE40	3432	40	32,9	750	3	6	4	-15°C +90°C	32

* Valor indicativo | Indicative value | Valeur indicative

ERFE Com Guia De Aço | ERFE Con Guia De Acero Semi Rigid With Steel Wire | Semi Rigide . Tire-fil En Acier



Tubo Jotagris "ERFE" com guia
Tubo Jotagris "ERFE" con guia
Semi-rigid conduit f. concrete with steel wire
Conduit semi-rigide ICTL
pour le beton avec tire-fil en acier



Médias
Medias
Medium loads
Jauge Medium



Fortes
Fuerτες
Heavy loads
Jauge fort



Ref.	Cod.	Diam. Ext.	Diam. Int. *	Newtons	Cod.	Joules	Cod.	Temp.	Cod.
ERFE16G	3432	16	12,4	750	3	6	4	-15°C +90°C	32
ERFE20G	3432	20	16,6	750	3	6	4	-15°C +90°C	32
ERFE25G	3432	25	20,6	750	3	6	4	-15°C +90°C	32
ERFE32G	3432	32	25,9	750	3	6	4	-15°C +90°C	32
ERFE40G	3432	40	32,9	750	3	6	4	-15°C +90°C	32

* Valor indicativo | Indicative value | Valeur indicative



SCAN + INFO