

JSL – Material Eléctrico, S.A.

Product: Bends for Rigid VD LH Conduit
Reference: C-16 VDLH_M0 | C-20 VDLH_M0 | C-25 VDLH_M0 |
 C-32 VDLH_M0 | C-40 VDLH_M0 | C-50 VDLH_M0 |



Ref.	Tube	Ø mm	Unit/bag	Weight Kg
C-16 VDLH_M0	VD16	16	50	0,2
C-20 VDLH_M0	VD20	20	50	0,5
C-25 VDLH_M0	VD25	25	5	0,1
C-32 VDLH_M0	VD32	32	5	0,18
C-40 VDLH_M0	VD40	40	5	0,28
C-50 VDLH_M0	VD50	50	3	0,43

PRODUCT CHARACTERISTICS

Type of Material	Thermoplastic	Color Available	Grey Cream Black White
Classification code	3432	Electrical properties	Electrical insulation
IP	66	Chemical properties	Resistant to acid & alkaline solutions
Self-extinguishing	960 °C		Resistance limited to solvents
Class	M0		UV Resistant
Operating temperature	-15°C +90°C	Others	Halogen free
			Flame retardand

APPLICABLE STANDARDS

EN 61386 - Conduit systems for cable management
 EN 60695 - Fire hazard testing. Glowing/hot-wire based test methods
 EN 60529 - Degrees of protection provided by enclosures (IP code)

