



MADE OF POLYAMIDE 6.6. DETECTABLE BY METAL DETECTOR AND X-RAY EQUIPMENT

- IT** REALIZZATE IN POLIAMMIDE 6.6. RILEVABILI DA APPARECCHIATURE METAL DETECTOR E RAGGI X
FR EN POLYAMIDE 6.6. DÉTECTABLE PAR LES DÉTECTEURS DE MÉTAL ET LES ÉQUIPEMENTS À RAYONS X
ES DE POLIAMIDA 6.6. DETECTABLES POR DETECTORES DE METALES Y EQUIPOS DE RAYOS X
DE DIE KABELBINDER AUS POLYAMID 6.6 KÖNNEN VON METALLDETEKTOREN UND RÖNTGENSTRAHLGERÄTE DETEKTIERT WERDEN

						
100×2,5	5.000	100	2 ÷ 24	80 N / 8 kg	●	DET.11.2102R
140×3,5	5.000	100	2,5 ÷ 36	160 N / 16 kg	●	DET.11.2110R
200×4,5	5.000	100	3 ÷ 51	200 N / 20 kg	●	DET.11.2123R
250×4,5	5.000	100	5 ÷ 68	200 N / 20 kg	●	DET.11.2124R
280×4,5	5.000	100	5 ÷ 76	200 N / 20 kg	●	DET.11.2140R
380×4,5	3.500	100	5 ÷ 110	200 N / 20 kg	●	DET.11.2127R
360×7,5	1.500	100	5 ÷ 101	500 N / 50 kg	●	DET.11.2134R

OTHER SIZES AVAILABLE UPON REQUEST | ALTRE MISURE DISPONIBILI SU RICHIESTA



CABLE TIES MADE OF POLYPROPYLENE (UL94:HB) ARE HIGHLY RESISTANT TO CHEMICALLY AGGRESSIVE ENVIRONMENTS AND ACIDS

- IT** REALIZZATE IN POLIPROPILENE (UL94:HB). ELEVATA CAPACITÀ DI RESISTENZA AD AMBIENTI CHIMICI AGGRESSIVI E AGLI ACIDI
FR LES COLLIERS DE SERRAGE EN POLYPROPYLÈNE (UL94:HB) SE DISTINGUENT PAR LEUR EXCELLENTE RÉSISTANCE AUX ENVIRONNEMENTS CHIMIQUES AGRESSIFS ET AUX ACIDES
ES LAS BRIDAS PARA CABLES DE POLIPROPILENO (UL94:HB) SE CARACTERIZAN POR UNA ALTA CAPACIDAD DE RESISTENCIA A ENTORNOS QUÍMICOS AGRESIVOS Y ÁCIDOS
DE DIE KABELBINDER AUS POLYPROPYLEN (UL94:HB) SIND GEGEN AGGRESSIVE CHEMISCHE UMGEBUNGEN UND SÄUREN BESTÄNDIG

						
100×2,5	30.000	100	2 ÷ 24	45 N / 4,5 kg	○	SEL.P2.202
140×3,5	20.000	100	2,5 ÷ 36	90 N / 9 kg	○	SEL.P2.210
200×4,5	10.000	100	3 ÷ 51	110 N / 11 kg	○	SEL.P2.223
250×4,5	10.000	100	5 ÷ 68	110 N / 11 kg	○	SEL.P2.224
280×4,5	10.000	100	5 ÷ 76	110 N / 11 kg	○	SEL.P2.425
360×4,5	8.000	100	5 ÷ 101	110 N / 11 kg	○	SEL.P2.426
380×4,5	7.000	100	5 ÷ 110	110 N / 11 kg	○	SEL.P2.427
360×7,5	3.000	100	5 ÷ 101	270 N / 27 kg	○	SEL.P2.434

OTHER SIZES AVAILABLE UPON REQUEST | ALTRE MISURE DISPONIBILI SU RICHIESTA

